南 通 万 诚 钢 绳 有 限 公 司
NANTONG WANCHENG STEEL ROPE CO., LTD.

MILL TEST CERTIFICATES

Date: Feb.14,2022

Client: ELITE SALES, INC.
Order No.: PO.No.802458 Contract No.:
Descriptions: STEEL WIRE ROPE SHIPPING TERM: CIF HOUSTON,TX,USA

Specification: RR-W-410D

Construction: 6X19+FC BRT. IPS Rope Diameter 1/2"
Reel Length: 6x5000' Quantity: 6 Reels

Lay Direction: RHRL Lay Length: RHRL
Reel No.: Part No.:
Min. Breaking Strength 21400LBS
Reel Markings: N/M

Test Results:

Rope Diameter:	0.522	inch
Preforming:	good	
Wt. of Zinc Coating:	N/A	g/sq.m
Breaking strength:	22598	LBS
Tensile Strength:	1870	N/mm2
Lubrication:	Dry	

Wire Rod Chemical Analysis (%)

C	Si	Mn	P	S
0.71	0.16	0.55	0.011	0.008

We hereby certify that the comodity is inspected according to the specification and foundgood in all respects as stated above.

Nantong Wancheng Steel Rope Co., Ltd.

南通万诚钢绳有限公司
NANTONG WANCHENG STEEL ROPE CO.,LTD

倪峰