COSMO WIRE LTD.

#4-10, KOYEON-RI, WOONGCHON-MYUN,
ULJU-KUN, ULSAN, KOREA

TEL : 82. 52. 261. 0478/9
FAX : 82. 52. 261. 0480

PHYSICAL AND CHEMICAL MILL TEST CERTIFICATE

ORIGINAL

D N V Det Norske Veritas
ISO 9001:2015 International Certification Registrar Ltd

DATE. : MAR/ 23/ 2023

Customer : ELITE SALES INC
P/O No. : 802707 Invoice No. : CMP-2022/126
L/C No. : Coated :
Quantity : 23 Reels Reel No. : 32 - 54

1. Type & Grade.

Diameter	3/8"	Construction	7 X 19
Length	5,000FT	Grade	
Specification	FS-RR-W-410F	Lubrication	DRY
Type	STAINLESS 304	Lay	R.H.O.L

2. Test Result.

ITEM	UNIT	SPEC.	ACTUAL
Diameter of Rope	INCH	0.375 - 0.401	0.380
Breaking Strength	LBS	12,000	12,560
Preforming			Good
Lay Length	MM		61.9
Wire Diameter	INCH	0.0240	0.0242
Zinc Weight	g/m2		

3. Chemical Analysis of Wire Rod (%)

Charge No	C	Si	Mn	P	S	Ni	Cr	Mo
S47116	0.035	0.42	1.56	0.033	0.004	8.02	18.25	

REMARKS :

We hereby certify that the above results are true and correct in every details.

Min Jong Kim

Manager of Quality Assurance Dept.
Test by : Min Jong Kim
E - Mail : cosmoro@naver.com